



HARDWARE CATALOG 2021



HARDWARE FOR INDOOR & OUTDOOR	6
PUSH Button	8
Camera Indoor – SH02	12
Camera Indoor – NG10	16
Camera Outdoor – NG07	20
Motion Sensor	24
Door /Window Sensor	28
Temperature Sensor	32
Water Leak Sensor	36
PUT Sensor	40
PLAY Sensor	44

SERVICE	48
Gateway – H38	50
Gateway – H80	54

ACCESSORIES	58
Holder for Motion Sensor	60
MagicPAD for Sensors	64
Cover for Camera Lens	68
Stand for Camera Outdoor	72
Rubber Cover for PUSH Button	86



**PUSH Button**  
Platform: NG05



**Camera Indoor**  
Platform: SH02



**Camera Indoor**  
Platform: NG10




**Camera Outdoor**  
Platform: NG07



**Motion Sensor**  
Platform: NG04



**Door /Window Sensor**  
Platform: NG01



**Temperature Sensor**  
Platform: NG03



**Water Leak Sensor**  
Platform: NG02



**PUT Sensor**  
Platform: NG12



**PLAY Sensor**  
Platform: NG30





# PUSH BUTTON

Whether switching camera recordings on and off or communicating the building status via voice output, the PUSH button is a true multi-talent.

Permanently mounted or mobile: the wireless and battery-powered PUSH button can be placed wherever it is needed – even on difficult surfaces. Or you can simply carry it with you around the premises within reach of the gateway.

	Platform: NG05		
		Status retrieval at the push of a button, multifunctionally assignable	



# PUSH BUTTON

The PUSH button with rubber cover in the color Aubergine



- Functions of sensors and cameras, e.g. start/stop recording, remote control
- Query the status of all sensors
- With rubber cover protected against splashing water on all sides (IP44) and suitable for outdoor use



The PUSH button in splash-proof outdoor use with rubber cover in the color May Green



Discreet attachment of the PUSH button on wood with rubber cover in the color Cappuccino




The PUSH button with rubber cover as a lifestyle accessory with function in the color Canary Yellow



Simplest one-push operation: one button, many functions

<b>PLATFORM</b>
NG05
<b>CONNECTIVITY</b>
Enhanced Green Power
<b>POWER SUPPLY</b>
1x 3.0 V CR2032 Battery
<b>OPERATING TEMPERATURE</b>
-10° to ≈ +50°C
<b>BATTERY LIFETIME</b>
Up to 3 years
<b>MEASUREMENT</b>
Ø 60 x 25 mm
<b>WEIGHT</b>
33 g
<b>FIXTURES</b>
None or adhesive strips










# CAMERA

## SH02

Keep an eye on all sensitive areas in the interior at all times. The intelligent camera detects important changes in the image. Alarm signals are detected with the built-in microphone. The integrated speaker is used for voice output.

	Platform: SH02		
		Only important moments are saved as a photo	
		Voice output of messages	
		Detection of learned alarm signals	





- Camera with infrared night vision function
- **New:** intelligent image analysis instead of video recordings without relevant content
- **New:** Camera can make hidden recordings with independent motion sensor
- **New:** integrated speaker for voice output for information or defense
- **New:** Microphone for intelligent alarm signal detection



Alarm signal detection

The camera in combination with the motion sensor expands the range of functions



The MagicPAD for tool-free mounting and dismounting of the camera on various surfaces



Cover for the camera lens for privacy without interfering with the speaker and microphone function



**PLATFORM**  
SH02

**RESOLUTION / VIEW ANGLE**  
2 MP / 85° hor., 85° vt.

**CONNECTIVITY**  
W-LAN 2,4 GHz

**MICROPHONE / SPEAKER**  
Yes / Yes

**INFRARED NIGHT VISION**  
Up to 5 m

**OPERATING TEMPERATURE**  
0° to +40°C

**POWER SUPPLY**  
Mains current


**MEASUREMENT**  
Ø 78 x 117 mm  
Cable length ≈ 150 cm

**WEIGHT**  
98 g

**CONNECTORS**  
- microSD Slot  
- Micro-USB (Power supply)  
- Reset button

**FIXTURES**  
Adhesive strips

Scale 1:2



Freely lockable tilt joint



Powerful speaker with built-in microphone



Optional usable mounting plate





# CAMERA

NG10

With the newly developed, robust 360° stand, positioning this camera in any corner of a room is easy.

The intelligent camera detects important changes in the image. Alarm signals are detected with the built-in microphone. The integrated speaker is used for voice output.

	Platform: NG10		
		Only important moments are saved as a photo	
		Voice output of messages	
		Detection of learned alarm signals	



# CAMERA

Small, smart, inconspicuous

The cover for the camera lens can be used temporarily or permanently



- The youngest member in our camera family
- Extended angle of view
- **New:** flexible 360° positioning
- **New:** improved image quality
- **New:** next generation speaker and microphone technology



Alarm signal detection



Camera in cooperation with a motion sensor – more depth of information saved

# CAMERA




<b>PLATFORM</b>	NG10
<b>RESOLUTION / VIEW ANGLE</b>	2 MP / 97° hor., 97° vt.
<b>CONNECTIVITY</b>	W-LAN 2,4 GHz
<b>MICROPHONE / SPEAKER</b>	Yes / Yes
<b>INFRARED NIGHT VISION</b>	Up to 5 m
<b>OPERATING TEMPERATURE</b>	-10° to ≈ +40°C
<b>POWER SUPPLY</b>	Mains current
<b>MEASUREMENT</b>	72 x 124 mm Cable length ≈ 150 cm
<b>WEIGHT</b>	111 g
<b>CONNECTORS</b>	- microSD Slot - Micro-USB (Power supply) - Reset button
<b>FIXTURES</b>	Adhesive strips



Combined ball and swivel joint up to 110° tilt and 360° rotation



Powerful speaker with built-in microphone





# CAMERA

## NG07

Keep an eye on the outside of your business at all times with an 82° viewing angle.

Thanks to artificial intelligence, the camera can distinguish important and unimportant events and only informs you when relevant changes are detected in the image.

	Platform: NG07		
		Only important moments are saved as a photo	
		Voice output of messages	
		Detection of learned alarm signals	



Easy to attach to almost any wall



- The smart camera now also for outdoor use
- **New:** special focal length for monitoring outdoor facilities
- **New:** next generation speaker and microphone technology
- **New:** IP65 dustproof and protected against water jets from any angle



Alarm signal detection



Camera stand for mounting and dismantling the camera on various surfaces without tools



Infrared night vision function





Powerful speaker with built-in microphone



Water repellent

<b>PLATFORM</b>	NG07
<b>RESOLUTION / VIEW ANGLE</b>	2 MP / 82° hor., 82° vt.
<b>CONNECTIVITY</b>	W-LAN 2,4 GHz
<b>MICROPHONE / SPEAKER</b>	Yes / Yes
<b>INFRARED NIGHT VISION</b>	Up to 15 m
<b>OPERATING TEMPERATURE</b>	-10° to ≈ +50°C
<b>POWER SUPPLY</b>	Mains current
<b>MEASUREMENT</b>	74 x 79 x 162 mm Cable length ≈ 270 cm
<b>WEIGHT</b>	515 g
<b>CONNECTORS</b>	- Reset button - USB (A) 2.0
<b>FIXTURES</b>	Screws





# MOTION SENSOR

Detect movement inconspicuously and be notified in seconds.

The highly sensitive infrared motion sensor reliably detects any movement indoors and is as inconspicuous as a lifestyle accessory.

	Platform: NG04		
		Detection of movements indoors	



# MOTION SENSOR

Mounting the motion sensor with the MagicPAD



Small and discreet



Reliably detects movements and is the optimal complement to a camera

- Highly sensitive infrared sensor for motion detection
- Sends notifications to your smart-phone when motion is detected
- In combination with a camera you get a photo on your smart-phone within seconds



Regulation of sensitivity (e.g. insects) by sensor shielding

# MOTION SENSOR

**PLATFORM**  
NG04

**VIEW ANGLE**  
80° hor., 80°vt. (40° with shielding)

**SENSING DISTANCE**  
Up to 5 m

**CONNECTIVITY**  
Enhanced Green Power

**INFRARED NIGHT VISION**  
Yes

**OPERATING TEMPERATURE**  
-10° to ≈ +50°C

**POWER SUPPLY**  
2x 1.5 V AA Battery


**BATTERY LIFETIME**  
Up to 3 years

**MEASUREMENT**  
63 x 46 x 40 mm

**WEIGHT**  
90 g

**FIXTURES**  
None

Scale 1:2





# DOOR/ WINDOW SENSOR

With our door/window sensor, you can easily and reliably monitor important doors and windows. File cabinets and restricted access areas can also be secured with this sensor. In doing so, you determine yourself whether you want to be notified about opening or closing.

	Platform: NG01		
		Open and close detection	



# DOOR/WINDOW SENSOR

Simple, discreet attachment to windows and doors



- Magnetic sensor to control items that can be opened and closed
- Immediately sends a notification to your smartphone when the open/close status changes
- Can output an indication as a voice message in combination with a camera in the event of a change of state



Secures not only doors and windows, but also cabinets and drawers



The door/window sensor as a power-saving aid on the refrigerator

# DOOR/WINDOW SENSOR



**PLATFORM**  
NG01

**CONNECTIVITY**  
Enhanced Green Power

**OPERATING TEMPERATURE**  
-10° to ≈ +50°C

**POWER SUPPLY**  
1x 3.0 V CR2032 Battery

**BATTERY LIFETIME**  
Up to 3 years

**MEASUREMENT**  
60 x 43 x 12 mm

**WEIGHT**  
24 g


**FIXTURES**  
Adhesive strips



Reliable magnetic sensor technology



Long battery life, easy maintenance





# TEMPERATURE SENSOR

Keep an eye on temperature changes in heat- or cold-sensitive areas at all times.

With our temperature sensor, you can easily and reliably monitor sensitive areas and receive direct notification when the defined temperature range is exceeded.

	Platform: NG03		
		Detection of temperature changes	



# TEMPERATURE SENSOR

Easy monitoring of the room temperature



- Sensor for temperature monitoring in closed rooms
- Immediately sends a notification to your smartphone when the temperature exceeds or falls below the defined range
- In combination with a camera, can issue an alert as a voice message in the event of an overshoot/undershoot



Easy to attach with included adhesive strips – even on uneven surfaces

# TEMPERATURE SENSOR




- PLATFORM**  
NG03
- CONNECTIVITY**  
Enhanced Green Power
- OPERATING TEMPERATURE**  
-10° to ≈ +50°C
- POWER SUPPLY**  
1x 3.0 V CR2032 Battery
- BATTERY LIFETIME**  
Up to 2 years
- MEASUREMENT**  
60 x 31 x 12 mm
- WEIGHT**  
18 g
- FIXTURES**  
Adhesive strips



Reliable, precise technology, uncomplicated operation



Long battery life, easy maintenance








# WATER LEAK SENSOR

Be automatically informed about leaking water or critical water levels.

Too much water or no water? You can decide what you want to keep an eye on.

	Platform: NG02		
		Detection of leaking liquids	



# WATER LEAK SENSOR

Monitoring of water levels with notification function



Detect leaking liquids in time

- Sensor for detection of fluid leakage/lack of fluid
- Immediately sends a notification to your smart phone when a fluid leakage/lack of fluid is detected
- In combination with a camera, can issue an alarm as a voice message in the event of fluid leakage/lack of fluid

# WATER LEAK SENSOR




- PLATFORM**  
NG02
- CONNECTIVITY**  
Enhanced Green Power
- OPERATING TEMPERATURE**  
-10° to ≈ +50°C
- POWER SUPPLY**  
1x 3.0 V CR2032 Battery
- BATTERY LIFETIME**  
Up to 3 years
- MEASUREMENT**  
60 x 31 x 12 mm  
View Angle ≈ 110 cm
- WEIGHT**  
27 g
- FIXTURES**  
Adhesive strips



Metal contacts



Long battery life, easy maintenance







# PUT SENSOR

Perhaps the smartest scale in the world.  
With the PUT sensor you can easily detect over/under weight.

	Platform: NG12		
		Detection of weight changes	



# PUT SENSOR

Detect level undershoot  
based on measured weight



- Sensor for measuring weight up to 5 kg with exchangeable carrier plate made of different materials
- Immediately sends a notification to your smartphone when weight over/under is detected
- In combination with a camera, can issue an alert as a voice message when the weight is exceeded/fallen short of



Interchangeable carrier plate in various colors and materials



Modern and sleek design

# PUT SENSOR



- PLATFORM**  
NG12
- CONNECTIVITY**  
Enhanced Green Power
- OPERATING TEMPERATURE**  
-10° to ≈ +40°C
- POWER SUPPLY**  
2 x 3.0 V CR2032 Battery
- BATTERY LIFETIME**  
Up to 1 year
- MEASUREMENT**  
Ø 125 x 19 mm
- WEIGHT**  
165 g
- FIXTURES**  
None



Replaceable carrier plate in wood look



Weigh up to 5 kg in precise 1 g increments







# PLAY SENSOR

The smart speaker with built-in microphone to detect alarm signals and output voice messages.

	Platform: NC30		
		Voice output of messages	
		Detection of learned alarm signals	



PLAY in combination with a door/window sensor



- Microphone to detect alarm signals and send notification to the smartphone of the person in charge
- Speaker to output voice messages, e.g. when the status of a sensor changes
- Immediately sends a notification to your smart phone when an alarm signal is detected



PLAY for the detection of alarm signals



PLAY with the H80 Gateway




<b>PLATFORM</b>	NG30
<b>CONNECTIVITY</b>	USB
<b>MICROPHONE / SPEAKER</b>	Yes / Yes
<b>OPERATING TEMPERATURE</b>	-10° to ≈ +40°C
<b>POWER SUPPLY</b>	Passive via Gateway (Micro-USB)
<b>MEASUREMENT</b>	Ø 60 x 32 mm View Angle 1 ≈ 25 cm View Angle 2 ≈ 150 cm
<b>WEIGHT</b>	55 g
<b>CONNECTORS</b>	- Micro-USB (Power supply)
<b>FIXTURES</b>	None or adhesive strips



Speaker openings



Micro-USB port





**Gateway**  
Platform: H38

50



**Gateway**  
Platform: H80

54





# GATEWAY

H38

The intelligent gateway is the central controller to which the cameras and sensors are connected.

All camera and sensor data is analyzed on the gateway so that only relevant data is processed further.

	Platform: H38		
		Control of the hardware and the service	




- Connect up to 40 sensors and three cameras
- Artificial intelligence for the recognition of alarm signals
- Filters irrelevant information, notifies you within seconds and ensures that you never miss an important moment again

Gateway in combination with the door /window sensor



Gateway with Camera and PLAY

Gateway with PUSH button




- PLATFORM**  
H38
- CONNECTIVITY**  
- Enhanced Green Power  
- LAN  
- USB
- OPERATING TEMPERATURE**  
0° to +40°C
- POWER SUPPLY**  
Mains current
- MEASUREMENT**  
35 x 170 x 122 mm
- WEIGHT**  
245 g
- CONNECTORS**  
- DC IN  
- microSD Slot  
- RJ45 (10/100 MBit)  
- Service Port (3.5 mm)  
- 2x USB (A) 2.0



Gateway front panel with on/off button and status LED



Gateway back side with connections







# GATEWAY

H80

The intelligent gateway is the central controller to which the cameras and sensors are connected.

All camera and sensor data is analyzed on the gateway so that only relevant data is processed further.

	Platform: H80		
		Control of the hardware and the service	

Gateway with motion sensor




- Connect up to 80 sensors and five cameras
- Artificial intelligence for the recognition of alarm signals and persons
- Filters irrelevant information, notifies you within seconds and ensures that you never miss an important moment again



Gateway and Camera



Gateway and PLAY



- PLATFORM**  
H80
- CONNECTIVITY**  
- Enhanced Green Power  
- LAN
- OPERATING TEMPERATURE**  
0° to +40°C
- POWER SUPPLY**  
Mains current
- MEASUREMENT**  
27 x 170 x 120 mm
- WEIGHT**  
235 g
- CONNECTORS**  
- Audio Port (3.5 mm)  
- DC IN  
- microSD Slot  
- Reset button  
- RJ45 (10/100 MBit)  
- Service Port (2.5 mm)  
- USB (A) 2.0  
- USB (A) 3.0




Gateway back side with reset button



Gateway back side with connections


Scale 1:3









**Holder for Motion Sensor**  
Model: NG97.09



**MagicPAD for Sensors**  
Model: NG97.01



**Cover for Camera Lens**  
Productnumber: 3E96.10.AA



**Stand for Camera Outdoor**  
Model: NG97.06



**Rubber Cover for PUSH Button**  
Various colors

# HOLDER FOR MOTION SENSOR

The holder for the motion sensor enables quick and easy mounting of the sensor on walls and inaccessible places.





# HOLDER FOR MOTION SENSOR

Attachment of the motion sensor  
in difficult places



- Wall bracket to hold the motion sensor
- Suitable for indoor and outdoor use
- Increases the monitoring radius



Discreet mounting of the sensor on the wall



**MODEL**  
NG97.09

**MEASUREMENT**  
Ø 72 x 129 mm

**WEIGHT**  
81 g

**FIXTURES**  
Screws




Combined ball and swivel  
joint up to 110° tilt and 360°  
rotation



The clamp can be screwed  
horizontally and vertically on  
the base



Water repellent







# MAGICPAD FOR SENSORS

The reusable silicone pad adheres to various surfaces and allows you to mount cameras and sensors without tools.

 	Modell: NG97.01 – MagicPAD		
		Mounting of sensors without drilling and gluing	





- Self-adhesive pad for mounting sensors and cameras on various surfaces
- Can be cleaned with water and reused
- Adheres to surfaces made of glass, wood and metal, among others

Mounting the motion sensor on wood with the MagicPAD



Fixing the PUSH button on glass with the MagicPAD



Fixing the temperature sensor on woodchip wallpaper with the MagicPAD



**MODEL**  
NG97.01

**OPERATING TEMPERATURE**  
-10° to ≈ +40°C

**MEASUREMENT**  
Ø 80 x 3 mm

**WEIGHT**  
14 g

**FIXTURES**  
Self-adhesive




Tool-free mounting on various surfaces



Washable and reusable


Scale 1:2







# COVER FOR CAMERA LENS


Visible privacy protection without limiting other camera functions. Reusable and compatible with all camera models.





Platform: 3E96 for cameras





Cover of camera lens for the protection of privacy






- Camera cover for visible privacy protection
- Unrestricted use of the alarm detection and voice output function
- Reusable and compatible with all camera models

Cover of SH02 camera lens



Cover of NG07 camera lens

Self adhesive and reusable



**PLATFORM**  
3E96 for cameras

**MEASUREMENT**  
Ø 20 x 2 mm

**WEIGHT**  
1 g


**FIXTURES**  
Adhesive surface



Covers in double sheet



Water repellent





# STAND FOR CAMERA OUTDOOR

Height adjustable camera Stand for indoor and outdoor,  
compatible with outdoor camera.





# STAND FOR CAMERA OUTDOOR

Height adjustable



Use on an lawn



Unobtrusive mounting of the camera in a flower pot

- Height adjustable camera stand for indoor and outdoor use
- Compatible with the camera for outdoor
- Impact tip for sticking into lawn and gravel bed



# STAND FOR CAMERA OUTDOOR

**PLATFORM**  
NG97 for camera outdoor

**MEASUREMENT**  
Ø 75 x 650 to 1150 mm

**WEIGHT**  
340 g

**FIXTURES**  
Stucked in or tied on




Secure mounting of the camera by screwing it to the base plate



Replaceable base plate



Water repellent







# RUBBER COVER FOR PUSH BUTTON

Sturdy rubber cover for the PUSH button to protect against splashing water from all sides (IP44) and suitable for outdoor use.





# RUBBER COVER FOR PUSH BUTTON



PUSH rubber cover in the colors Cappuccino and Aquamarine



PUSH rubber cover in the colors Pink and Pale Lime



# RUBBER COVER FOR PUSH BUTTON



**PLATFORM**  
NG97 for PUSH button

**OPERATING TEMPERATURE**  
-10° to ≈ +50°C

**MEASUREMENT**  
Ø 75 x 30 mm

**WEIGHT**  
39 g



**FIXTURES**  
None or adhesive strips



Suitable for outdoor



Protection against splashing water from all sides (IP44)
















	Cappuccino		Pink		Grey
	Corall		Lilac		
	Pale Lime		Canary Yellow		
	May Green		Dark Blue		
	Aquamarine		Aubergine		
	Light Cyan		Deep Purple		

All color specifications without guarantee – deviations possible.



# SYMBOLS MARK OF CONFORMITY

The following table contains a generally non-binding description of symbols and mark of conformity.  
The mark of conformity are placed on the products according to testing and testing possibility.

Symbol Mark of conformity	Description	Symbol Mark of conformity	Description
	CE/RED – Product with this marking is subject to the applicable CE/RED directives of the EU		suitable for indoor use
	WEEE Directive 2012/19/EU This device is subject to the regulation of waste equipment disposal		suitable for indoor and protected outdoor use
	RoHS – Restriction of the use of certain Hazardous Substances in electrical and electronic equipment		Good to know
	REACH-SVHC – Chemical composition tested according to EU Directive 2018/851 and EU Directive 1907/2006		Accessories for hardware expansion
	MIC/TELEC This device is subject to wireless product certification in Japan		Further, additional information
	RCM – reliability-oriented maintenance This device is subject to RCM - Reliability Centered Maintenance		
	IP44 This device is protected against solid foreign bodies with diameter ≥ 1.0 mm, protected against access with a wire, protection against splash water from all sides		
	IP65 This device is dustproof, full protection against contact, protection against water jets (nozzle) from any angle		


## Hardware Catalog – Edition April 2021

320EAST GmbH  
An der RaumFabrik 31b  
76227 Karlsruhe, GERMANY

mail: [sales@320east.de](mailto:sales@320east.de)  
phone: +49 721 90 98 96 0  
fax: +49 721 90 98 96 99

Limited liability company  
Registered office of the company: Karlsruhe  
Local court Mannheim HRB 731424  
Managing Director: Heiko Schneefeld

© Copyright 2021 by 320EAST GmbH

The logo  is a registered trademark of 320EAST GmbH.

320EAST GmbH reserves all rights to it.  
All other trademarks are the property of their respective owners.

This work is protected by copyright. Its use outside the narrow limits of copyright law is not permitted without the consent of the publisher and is punishable by law. This applies in particular to reproduction, translation, microfilming and storage and processing in electronic systems. All rights reserved.

Subject to technical changes. Product illustrations may differ.

## Image credits

atbo-245219   pexels	8 – 9
norma-mortenson-4391470   pexels	20 – 21
ricardo-esquivel-2226607   pexels	60 – 61
florencia-potter-351300   pexels	62
polina-tankilevitch-3735213   pexels	62
nastuh-abootalebi-yWwob8kwOck   unsplash	68 – 69
Product renderings   More Zhang	
Technical product drawings   Tim Zierlein	
Product and architectural photography   Jürgen Lenhardt	





320EAST GmbH  
An der RaumFabrik 31b  
76227 Karlsruhe, GERMANY

mail: [sales@320east.de](mailto:sales@320east.de)  
phone: +49 721 90 98 96 0  
fax: +49 721 90 98 96 99